


	<u>ENGLISH</u>	<u>SI</u>	
Performance			
Number of Conductors	4	4	
Cable Style	Multi Conductor - Shielded	Multi Conductor - Shielded	
Environmental			
Temperature Range	-130 to 392 °F	-90 to 200 °C	
Electrical			
Capacitance(conductor to conductor @ 70 °F (21 °C))	18 pF/ft	52.4 pF/m	
Capacitance(conductor to shield / drain @ 70 °F (21 °C))	28 pF/ft	84.6 pF/m	
Voltage Rating(rms - maximum V)	160 V	160 V	
Physical			
Cable Jacket Diameter	0.063 in	1.60 mm	[1]
Cable Jacket Material	FEP	FEP	
Cable Jacket Color	Green	Green	
Conductor Style	Stranded - 7 Strands 44 AWG	Stranded - 7 Strands 44 AWG	
Conductor Material	Silver Plated Copper Alloy	Silver Plated Copper Alloy	
Conductor Diameter(32 AWG)	0.008 in	0.203 mm	[1]
Insulation Material Over Conductor(s)	Extruded TFE	Extruded TFE	
Shield Type Over Bundle	Braid: 85% Minimum Coverage	Braid: 85% Minimum Coverage	
Shield Material Over Bundle	Silver Plated Copper	Silver Plated Copper	
Shield Wire Diameter Over Bundle(Each Strand 38 AWG)	0.077 in	1.95 mm	[1]
Bend Radius(minimum)	1 in	25.4 mm	
Weight	0.065 oz/ft	6 gm/m	[2]
<i>All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.</i>			
ICP® is a registered trademark of PCB Group, Inc.			

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

NOTES:
 [1] Nominal.
 [2] Typical.

Entered: LK	Engineer: BAM	Sales: ML	Approved: BAM	Spec Number:
Date: 10/5/2016	Date: 10/5/2016	Date: 10/5/2016	Date: 10/5/2016	55241



3425 Walden Avenue, Depew, NY 14043

Phone: 716-684-0001
Fax: 716-684-0987
E-Mail: info@pcb.com