

	ENGLISH	SI
Performance		
Connector Style	Pigtail	Pigtail
Connector Style	BNC	BNC
Connection Type	Plug (male pin)	Plug (male pin)
Coupling Method	Bayonet	Bayonet
Strain Relief	Heat Shrink	Heat Shrink
Environmental		
Temperature Range	-67 to +230 °F	-55 to +110 °C
Physical		
Electrical Connections	"See Outline Drawing"	"See Outline Drawing"
ROHS Compliant	Yes	Yes

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

NOTES:

Entered: ND	Engineer: GD	Sales: BS	Approved: BAM	Spec Number:
Date: 04/06/2022	Date: 04/06/2022	Date: 04/06/2022	Date: 04/06/2022	76158

All specifications are at room temperature unless otherwise specified.
 In the interest of constant product improvement, we reserve the right to change specifications without notice.

 <p style="margin: 0;">PCB PIEZOTRONICS AN AMPHENOL COMPANY</p>	<p style="margin: 0; font-size: 0.8em;">Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com</p>
<p style="margin: 0; font-size: 0.8em;">3425 Walden Avenue, Depew, NY 14043</p>	