

Performance	ENGLISH	SI	
Measurement Range(Full Scale Capacity)	36,000 in-lb	4,067 Nm	[1]
Sensitivity(output at rated capacity)	2.0 mV/V	2.0 mV/V	[1][2]
Non-Linearity	≤ 0.05 % FS	≤ 0.05 % FS	[2]
Hysteresis	≤ 0.05 % FS	≤ 0.05 % FS	[2]
Non-Repeatability	≤ 0.02 % FS	≤ 0.02 % FS	[2]
Environmental			
Overload Limit	60,000 in-lb	6,775 Nm	
Temperature Range(Operating)	-65 to 170 °F	-54 to 77 °C	
Temperature Range(Compensated)	+70 to +170 °F	+21 to 77 °C	
Temperature Effect on Output(Maximum)	± .002 %Reading/°F	± .0036 %Reading/°C	[3]
Temperature Effect on Zero	± .002 %FS/°F	± .0036 %FS/°C	[3][2]
Balance(Maximum)			
Electrical			
Excitation Frequency	3.28 kHz	3.28 kHz	
Bridge Resistance	350 Ohm	350 Ohm	[1]
Excitation Voltage	2 to 10 VAC rms	2 to 10 VAC rms	[4]
Bridge Current(at 5 VAC)	50 mA	50 mA	
Insulation Resistance	> 5,000 MOhm	> 5,000 MOhm	
Zero Balance	≤ 1 % FS	≤ 1 % FS	[2]
Physical			
Size (Shaft Length x Housing Length x Housing Height)	15.75 in x 8.25 in x 5.50 in	400.1 mm x 209.6 mm x 139.7 mm	[5]
Weight	40 lb	18.2 kg	
Mounting	2.25 in Dia. Keyed Shaft	57.2 mm Dia. Keyed Shaft	
Sensing Element	Strain Gage	Strain Gage	
Housing Material	Black Oxided Steel	Black Oxided Steel	
Shaft Material	Steel	Steel	
Electrical Connector	MS3102A-14S-5P	MS3102A-14S-5P	
Torsional Stiffness	11,800 kin-lb/radian	1,330 kN-m/radian	
Rotating Inertia	0.036 in-lb-sec <sup>2</sup>	0.004 N-m-sec <sup>2</sup>	
Maximum Speed	6,700 RPM	6,700 RPM	

**OPTIONAL VERSIONS**

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

**NOTES:**

[1]Nominal.  
 [2]FS - Full Scale.  
 [3]Over compensated operating temperature range.  
 [4]Recommended 10 VAC RMS.  
 [5]See Outline Drawing 24650 for Complete Dimensions  
 [6]See PCB Declaration of Conformance PS062 for details.

**SUPPLIED ACCESSORIES:**

Model 180-019A 5-socket mating connector for Series 3100, 4100, 4200 torque sensors (1)  
 Model 8113-105A Relay activated precision shunt calibration module (1)



All specifications are at room temperature unless otherwise specified.  
 In the interest of constant product improvement, we reserve the right to change specifications without notice.

Entered: ND	Engineer: PE	Sales: BS	Approved: JM	Spec Number:
Date: 06/10/2022	Date: 06/10/2022	Date: 06/10/2022	Date: 06/10/2022	19115

 <b>PCB LOAD &amp; TORQUE</b> A PCB PIEZOTRONICS DIV.	<b>PCB Load &amp; Torque A Division of PCB Piezotronics</b> 24350 Indoplex Circle Farmington Hills, MI 48335 UNITED STATES Phone: 866-684-7107 E-Mail: <a href="mailto:LTSales@pcb.com">LTSales@pcb.com</a> Web site: <a href="http://www.pcb.com/LoadAndTorque">www.pcb.com/LoadAndTorque</a>
---	---